



2720 111°52'30" 39°00" 419000 N 415 414 413 57'30" 412 411 409 408 55' 407 406 405 404 200 000 FEET 23 24 25 26 27 28 29 30 31 32 33 34 35 36

38°52'30" 111°52'30" 425 426 427 428 429 430 431 47'30" 432 433 1 920 000 FEET 434 111°45' 39°00" 2721

38°52'30" 111°52'30" 425 426 427 428 429 430 431 47'30" 432 433 1 920 000 FEET 434 111°45' 39°00" 2821

36875
 36875
 36875

Mapped, edited, and published by the Geological Survey
 Control by USGS and USC&GS
 Topography by photogrammetric methods from aerial photographs taken 1963. Field checked 1966
 Polyconic projection. 1927 North American datum
 10,000-foot grid based on Utah coordinate system, central zone
 1000-meter Universal Transverse Mercator grid ticks, zone 12, shown in blue
 Fine red dashed lines indicate selected fence lines
 Areas covered by dashed light-blue pattern are subject to controlled inundation

UTM GRID and 1966 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24,000
 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
 1 0 1 1 KILOMETER

CONTOUR INTERVAL 40 FEET
 DOTTED LINES REPRESENT 10-FOOT CONTOURS
 DATUM IS MEAN SEA LEVEL

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
 FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242
 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION
 Heavy-duty ——— Light-duty - - - - -
 Medium-duty ——— Unimproved dirt - - - - -
 U.S. Route (red square) State Route (red circle)

QUADRANGLE LOCATION
 UTAH

SALINA, UTAH
 N3852.5—W11145.7/5
 1966
 AMS 3661 IV NE—SERIES V897